

Hanwha Electronic Blasting System II (HEBS-II)

Description

Hanwha Electronic Blasting System II (HEBS-II) consists of:

- HiTRONIC II™ Electronic Detonator
- Blaster
- Logger
- Planner
- Harness Wire

HEBS-II is designed to maximize blasting performance by utilising advanced electronic technology. HEBS-II can be handled easily and has safety and reliability features to protect against electromagnetic pulse (EMP) and stray current.

HiTRONIC II™ electronic detonators are programmable and reprogrammable from 0ms to 50,000ms in 1ms intervals, so the system can deliver a range of timing/blasting options with high accuracy and precision.

HEBS-II is suitable for use in underground, quarry and open pit environments as well as controlled blasting applications requiring timing control and accuracy.

HiTRONIC II™ electronic detonators should be used with Blaster, Logger and Planner units specific to HEBS-II.




Features & Benefits

- Fully Programmable, accurate and precise electronic delay timing for maximum 50,000ms
- Duplex type harness wire to easy connect
- Using three types (Logging, Tagging, Scanning) to read detonator ID
- Remote Firing up to 5km (Line of Sight)
- Two-way communication and testing functions; delay time programming, connection and circuit testing

- Enhanced safety and security achieved via Planner and Logger with the ability to read unique detonator ID numbers and unique communication protocol and dual capacitors for programming and blasting
- Inherently safe with multiple inbuilt redundancies and safety mechanisms
- High portability and usability with a weight of less than 2kg per Set (Blaster, Logger and Planner)

Technical Data

HiTRONIC II™

HiTRONIC II™			
Wire Type	Standard		Heavy duty
	Folded	Spooled	Bobbin-less
Packing Method			
Length of Wire	6-18 m	15-30 m	6-80m
	(Custom made length possible)		
Base Charge		PETN, #8 (730mg)	
Primary Charge		DDNP	
Shell	Material	Copper	
	Dimension	ø7.5mm x 90mm	
Barcode Type		QR code	
Programmability		1 ms	
Maximum Delay Time		50,000 ms	
Accuracy		CV 0.02%	
Spool size		Height: 42mm Outer Diameter: 90mm	
Tensile strength		Standard: 25 kgf, Heavy duty: 50 kgf	
Wire Color		Standard: Yellow Heavy duty :Green	
Operating Temperature		-30 to +70 °C	
Storage Temperature		-30 to +50 °C	
Transport Temperature		-40 to +70 °C	
Water resistance		Standard: 7bar, 48hrs Heavy duty: 7bar, 120hrs	
Drop weight impact		EN13763-11	
Electrostatic Discharge Resistance		Wire to wire : 2,500pF at 30kV Wire to shell : 2,500pF at 30kV	

* Contact Hanwha's technical representatives for custom made lengths

* Bobbin-less products are packed in PE shrinking wrap.

Hanwha Electronic Blasting System II (HEBS-II)

Revised on: June 19th, 2020 (Ver 1.4)
www.hanwhacorp.co.kr/eng/explosives

Hanwha Electronic Blasting System II (HEBS-II)

Blaster

Blaster	
Appearance	
Dimension	242 x 189 x 52 mm
Maximum Detonator Capacity	Stand-alone mode : 3,000 detonators per blast Multiple blast mode : 21blasters, 63,000 detonators
Maximum Wireless Range without Repeater	5km, Line of Sight
Maximum Lead in Wire	2,000 m
Weight	1.45 kg
Operating Temperature	-20 to +60 °C
Storage/Transport Temperature	-30 to +60 °C
Charge Temperature	0 to +45 °C
Battery	7,000mAh@12.6V, Rechargeable
Splash proof	IP65


***Need to consult with the technician about maximum operating distance and detonator quantity**

Planner

Planner	
Appearance	
Dimension	155 x 75.5 x 18.6 mm
Maximum Detonator Capacity	1,000 per Planner
Weight	249 g
Operating Temperature	-20 to +50 °C

Storage/Transport Temperature	-40 to +70 °C
Charge Temperature	0 to +40 °C
Battery	4,300mAh@3.6V DC Rechargeable Li-Ion
Electrostatic Discharge Resistance	+/-15kV Air, +/-8kV Contact, +/-8kV Charge body
Drop	Multiple 1.2m to tile over concrete over -10 to +50°C
Sealing	IP67 and IP65 per applicable IEC sealing specification

Logger

Logger	
Appearance	
Dimension	186 x 78.7 x 38.5 mm
Maximum Detonator Capacity	500 per Logger
Maximum Lead in Wire	2,000 m
Weight	330 g
Operating Temperature	-20 to +60 °C
Storage/Transport Temperature	-30 to +70 °C
Charge Temperature	0 to +40 °C
Battery	3,500mAh@8.4V, Rechargeable
Electrostatic Discharge Resistance	+/-15kV Air, +/-8kV Contact
Splash proof	IP65

TECHNICAL DATA SHEET



Hanwha Electronic Blasting System II (HEBS-II)

Harness Wire

Harness Wire			
Appearance			
	Length	250m/roll, 400m/roll	
Properties	Wire	Material	Copper
		Diameter	0.6mm
	Wire Insulation	Material	PE
		Outer Diameter	1.2mm
	Tensile strength	23kgf	
Resistance	0.075 Ω/m		

	30.0	20	7.9	9.4
	35.0	16	7.3	8.8
	40.0	12	6.3	7.8
	50.0	7	4.7	6.2
	60.0	6	6.9	8.4
	70.0	6	5.5	6.9
	80.0	5	5.4	6.8

Hazard classification

UN No. (Class / Division):	0030(1.1B) / 0456 (1.4S)
Proper Shipping Name	DETONATORS, ELECTRIC for blasting
EmS	F-B, S-X (1.1B / 1.4S)

Packaging

HiTRONIC II™ electronic detonators are available in the following packaging based on one box..

Grade		UN 0456 / 1.4S (470 X 295 X 160 mm)			
Type	Length (m)	Pcs/box	Net Weight (kg)	Gross Weight (kg)	
Standard	Folded	6.0	60	4.5	7.4
		9.0	50	5.0	7.7
		12.0	40	4.5	6.8
		15.0	30	4.2	6.1
		18.0	30	4.4	6.4
	Spooled	15.0	30	5.0	6.5
		20.0	30	6.0	7.5
		25.0	30	7.5	9.0
		30.0	30	8.5	10.0
		HD	Bobbin-less	6.0	42
9.0	36			4.8	6.2
12.0	30			5.2	6.6
15.0	30			6.0	7.5
20.0	28			7.6	9.1
25.0	22			7.3	8.8
30.0	18			7.1	8.6
35.0	16			7.3	8.8
40.0	14			7.3	8.8
50.0	14			9.1	10.6
60.0	12	9.5	11.0		
70.0	12	10.5	12.1		
80.0	10	10.6	12.2		

Grade		UN 0030 / 1.1B (470 X 295 X 120 mm)			
Type	Length (m)	Pcs/box	Net Weight (kg)	Gross Weight (kg)	
Standard	Folded	6.0	50	3.5	4.5
		9.0	40	4.0	5.0
		12.0	30	3.5	4.5
		15.0	20	3.0	4.0
		18.0	20	3.5	4.5
	Spooled	15.0	30	5.0	6.0
		20.0	30	6.0	7.0
		25.0	30	7.5	8.5
		30.0	30	8.5	9.5
		HD	Bobbin-less	6.0	48
9.0	36			4.8	6.2
12.0	30			5.2	6.6
15.0	25			5.0	6.4
20.0	23			6.3	7.8
25.0	20	6.7	8.2		

Usage Instructions

All of the HEBS-II equipment, including Blaster, Logger, Planner and Harness Wire, must only be used with HiTRONIC II™ electronic detonators. (Do not use this equipment with any other detonator, electric or electronic.) HEBS-II equipment can be safely operated at temperatures ranging from -20°C ~ +50°C.

HiTRONIC II™ electronic detonators must be handled with care, attention should be paid to protect the wire insulation during stemming and loading of the holes.

Hanwha Electronic Blasting System II (HEBS-II)

Access to and use of *HiTRONIC II™* electronic detonators should be restricted to trained and authorized personnel.

Safety

HiTRONIC II™ electronic detonators can be initiated by exposure to shock, impact, friction or heat.

HEBS-II components are designed to provide a high level of safety against static electricity, stray electrical currents and radio wave transmission. *HEBS-II* equipment must be kept safe from submersion in water and excessive impact.

Storage

All ignition sources, such as matches and lighters, are strictly prohibited within minimum of 8 meters radius of the detonators.

HiTRONIC II™ electronic detonators should be stored in a properly conditioned magazine of cool and dry atmosphere.

HiTRONIC II™ electronic detonators must be used within 12 months after opening the packaging. Detonators that are older than five years should not be used.

Store in a secure magazine, access to products and storage should be restricted to authorized personnel.

Delay detonators should be used in order of manufacturing date as they deteriorate with age. Use oldest stored product first.

HEBS-II devices (Blaster, Logger, and Planner) should be stored at 30% to 50% battery charge for long-term storage for 1 month or longer.

Be aware that when used below 0°C, *HEBS-II* device's battery service time may be significantly reduced.

Disposal

For disposal of explosive materials, please dispose of in accordance with relevant local and federal regulations or contact Hanwha regional technical manager for safe disposal.

Disclaimer

The information in this Technical Data Sheet is correct as of the date issued however, subject to periodic review. Hanwha reserves the right in its sole discretion and without prior written notice to modify the product(s) and/or specifications described herein ("Product"). Hanwha disclaims any warranties with respect to Product, the safety or suitability thereof, or the results to be obtained, whether express or implied, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of Product, some of which are uniquely within the user's knowledge and control, it is essential that the user

evaluate Product to determine whether it is fit for a particular purpose and suitable for the user's method of use or application.

The use of Product is an intrinsically dangerous activity and must be restricted to qualified and trained users in possession of any necessary permits and licenses, and comply at all times with appropriate safety and risk prevention measures and with applicable laws.

This document and any accompanying information is not intended to constitute – and shall not be construed as – an offer or contractual commitment on Hanwha's side. For further information about Product, please contact your distributor or sales representative directly.

Please contact the following offices for any emergency or enquiry.

Head Office (Korea)

Hanwha Corporation

Hanwha Building 17th floor
86 Cheonggyecheon-ro, Jung-gu
Seoul, Korea 04541

TEL. +82 2 729 1629

FAX. +82 2 729 1850

E-mail commercial@hanwha.com

HMS INDONESIA

PT. Hanwha Mining Services Indonesia

Talavera Office Park, Suite Area, 21th Floor
JL. TB Simatupang Kav 22 Cilandak
Barat Jakarta Selatan 12430

TEL. +62 21 2782 8378

FAX. +62 21 2782 8643

E-mail hmsindonesia@hanwha.com

HMS AUSTRALIA

Hanwha Mining Services Australia Pty Ltd

Level 9, 132 Arthur Street North Sydney NSW 2060
Australia

TEL. +61 416 770 529

Emergency 1800 054 055

E-mail australia@hanwha.com

HMS LATIN AMERICA

Hanwha Mining Services Chile

Alonso de Cordova 5870, Office 707, Las Condes,
Santiago, Chile

TEL. +56 2 2993 7546

E-mail hmschile@hanwha.com

Hanwha Electronic Blasting System II (HEBS-II)

HMS USA

Hanwha Mining Services USA

420 East South Temple Suite 260, Salt lake City

UTAH 84111, USA

TEL. +1 801 336 1553, 1602

FAX. +1 801 384 0567

E-mail leehw@hanwha.com

SOUTH AFRICA

Hanwha Corporation Johannesburg

Cedar Office estate Block 1, Unit 1A

Corner Stinkwood Cl & Cedar Rd broad acres

2021, Johannesburg, South Africa

TEL. +27 11 317 7300

FAX. +27 11 465 0499

E-mail yhlee@hanwha.com